

TAXIWAY ELEVATED EDGE LIGHT



RELATED STANDARDS

FAA : in accordance with FAA specifications AC-150/5345-46C L-861T

ICAO : in accordance with Annex 14, Vol.1 and Aerodrome Design Manual Part 4

NATO : in accordance with STANAG 3316

APPLICATIONS

As taxiway edge and apron edge light for runways of all categories.

FEATURES

- **Small size** helps resist heaviest jet blasts.
- **Easily mounted** with breakable coupling over a 2" muff pipe.
- **Adaptable to adverse environmental conditions** height can be increased in areas of heavy snowfall.
- **Watertight**
- **Needs less maintenance**, thanks to the minimum number of parts all simple and functional
- **Long lamp life** 1000 hours at full intensity (6.6A) increases to 2000-4000 hours in practice since the system usually operates at lower intensities.
- Available also with **LED** system.
- **Energy Saver** with its highly efficient optics that need 45W lamps.
- **10000h** LED life with high intensity less energy.

Product with	Manufacturer code
45w Halogen	TT.028.D.04.B
LED	TT.028.D.04.C

Manufacturer reserves the right to make alterations to the specifications



YAKINDOĞU OTOMOTİV YAPI
SAN ve TİC Ltd. Şti

5627/3 Sokak No.21 Camdibi 35090 Izmir

TEL:+90 232 4339878-7898

www.ydszeren.com Email: mail@ydszeren.com

